

TOP SECRET

Copy 108

7 Pages

25X1

March 1965

PHOTOGRAPHIC INTERPRETATION REPORT

LOW BLOW AND FLAT FACE RADAR TOWERS LENINGRAD SAM SITE B29-3, USSR




CIA



DIA

25X1

NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER



TOP SECRET

DDR-DUPE

25X1

TOP SECRET

25X1
25X1
25X1
25X1

PHOTOGRAPHIC INTERPRETATION REPORT

LOW BLOW AND
FLAT FACE RADAR TOWERS
LENINGRAD SAM SITE B29-3, USSR

March 1965

NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER

TOP SECRET

25X1
25X1
25X1

TOP SECRET

25X1

25X1

25X1




FIGURE 1. LOCATION OF Leningrad SAM SITE B29-3.

NPIC J-8663 (3/65)

TOP SECRET

25X1

25X1

TOP SECRET

25X1

25X1

25X1

This report has been prepared in response to CIA requirement C-SI4-82,098, requesting drawings and mensuration of 2 radar towers, one with a LOW BLOW and the other with a FLAT FACE radar, at Leningrad SAM Site B29-3 [redacted] located at 60-01-20N 29-41-30E, Figure 1), as covered by small-format photography of [redacted]

Figures 2 and 3 present detailed drawings of the towers, which are similar lattice towers with platforms on top and are located 600 feet apart.

guardrail. The height as determined from photography from [redacted] by the shadow method confirms this height to within [redacted]. The platforms of both towers are [redacted] above the ground and approximately [redacted] above tree level. The height above tree level of course varies with tree height; however, both tower platforms are well above the surrounding trees. The top of the LOW BLOW radar is [redacted] above ground level and approximately [redacted] above tree level, and the top of the FLAT FACE radar is [redacted] above ground level and approximately [redacted] above tree level.

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

Each tower has a guardrail completely enclosing the platform and guardrails around the first 2 sections below the platform; however, on the third section below the platform and possibly on the rest of the lower sections, guardrails appear only on the side near the stairs and do not completely enclose the section.

Although the LOW BLOW and FLAT FACE towers are similarly constructed and have the same dimensions, they differ in some respects. The LOW BLOW tower has 4 possible supports, 1 located on each corner of the platform. These supports are slightly higher than the radar and will possibly be used to support netting, sheeting, or some form of windbreak or weather protection. The LOW BLOW tower also has a possible structure or sheeting [redacted] enclosing 1 corner of the top section of the tower; the possible purpose of this enclosed corner cannot be determined. The FLAT FACE tower has neither the possible supports at the corners of the platform nor the enclosed corner of the top section. The LOW BLOW radar tower also has an unidentified long, narrow object, approximately [redacted] attached to the bottom of the platform directly below the radar. The FLAT FACE tower does not have such an object. The FLAT FACE tower does have what appear to be triangular "plates" or a solid triangular mass on either

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

TOP SECRET


25X1

25X1

TOP SECRET

25X1

25X1



25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

FIGURE 2. LOW BLOW RADAR TOWER.

NPIC J-8664 (3/65)

25X1

TOP SECRET


25X1

25X1

25X1

TOP SECRET

25X1
25X1
25X1



25X1
25X1
25X1
25X1
25X1
25X1
25X1

FIGURE 3. FLAT FACE RADAR TOWER.

NPIC J-8665 (3/68)

TOP SECRET

25X1
25X1
25X1

TOP SECRET

25X1
25X1
25X1



FIGURE 4. LOW BLOW RADAR TOWER, [REDACTED]



FIGURE 5. FLAT FACE RADAR TOWER, [REDACTED]

25X1
25X1

side of the central point where the angled support beams join the bottom of the platform; these triangular plates give a "bow tie" appearance to this portion of the top section of the tower. Both towers have 2 possible cables or cable conduits which appear to drop down from the platforms and through the centers of the

towers and probably connect the radars with their associated ground-located equipment. The cables or conduits at the FLAT FACE tower both have small diameters. The larger of the LOW BLOW tower cables or conduits [REDACTED] in diameter.

25X1
25X1

TOP SECRET

25X1

25X1

TOP SECRET

25X1
25X1
25X1

REFERENCES

25X1

MAPS OR CHARTS

ACIC. US Air Target Chart, Series 200, Sheet 0103-25HL, 3d ed, Jun 62, scale 1:200,000 (SECRET)

AMS. Series N501, Sheet NO 35-3, 2d ed, Jul 59, scale 1:250,000 (UNCLASSIFIED)

AMS. Series M515, Sheet NP 35, 36-14, 2d ed, Feb 63, scale 1:250,000 (UNCLASSIFIED)

AMS. Series N701, Sheet 4537 I, 1st ed, Sep 62, scale 1:50,000 (UNCLASSIFIED)

AMS. Series N701, Sheet 4538 III, 1st ed, Mar 60, scale 1:50,000 (UNCLASSIFIED)

RELATED DOCUMENTS

NPIC. R-183/63, *Towers at SA-3 SAM Sites, USSR*, Aug 63 (TOP SECRET)

25X1

Foreign Technology Division, Air Force Systems Command. FTD-TS-62-10, *Sino-Soviet Bloc Radar Systems - Ground Radar*, 9 Nov 62 (SECRET)

NPIC. R-862/64, *SA-3 SAM Site Towers, Kapustin Yar/Vladimirovka Missile Test Center and Leningrad Area, USSR*, Oct 64 (TOP SECRET)

25X1

NPIC. R-340/64, *Newly Identified SA-3 SAM Site Towers, Leningrad Area, USSR*, May 64 (TOP SECRET)

25X1

NPIC. R-236/63, *Search for Elevated Electronics Equipment at SA-3 SAM Sites, USSR*, Oct 63 (TOP SECRET)

25X1

REQUIREMENT

CIA. C-SI4-82,098

NPIC PROJECT

12035/64

TOP SECRET

25X1

25X1

Page Denied